

# EMCF1000

## Digital Wired Discussing Conference System



Uses fully digital circuit design, with a four-way parallel control output, able to connect a total of 60 microphone units, and with load and short circuit protection function, can also be connected to an extension machine to connect more units.



7 Meeting Modes available: FIFO (First In First Out), Limited Speech, Free Discussion, Chairman Only, LIFO (Last In First Out), VIE to Speak Mode (Voice Initiated Entry), Apply to Speak Mode.



Uses large LCD screen which displays system setting content. Front panel have few function keys for the system set up.



Number of speakers at a time can be chosen between 1-6 person. Can also choose to allow everyone to speak.



Can be controlled via a PC Software instead of the controller interface or both controllers used simultaneously, allowing effective interface management integration.



Built-in telephone coupler input and output ports, able to set as phone call and dial out, allowing remote voice conference.



Three kinds of audio output adaptable to connect with other audio device.

## SPECIFICATION

Model NO.	EMCF1000
Power Supply	AC 100-240 V 50 / 60HZ
Output impedance	RCA-200Ω
Input impedance	LINE-50 KΩ
	DIN-50 KΩ
S / N ratio	> 90 dB (1 KHz THD1%)
Case dimension	480 x 220 x 56 mm
Accessory	2 m 8 core shielded cable

## EMCF-1001L

### Chairman Unit



## EMCF-1002L

### Delegate Unit



Intelligent digital design control circuit which offers low power consumption;



Switch are designed as light touch, minimizing any noise when pressing.




High fidelity single directional capacitor microphone, sound restoration ability, high definition and low noise;



Contains built-in speaker, which can be used for conference amplification



The chairman unit has the priority to speak and can close other delegate units at any time;



Touching the switch volume control button to adjust the volume;



With internal magnetic high fidelity speaker, it will automatically mute after opening the microphone, which is not easy to produce whistling;



Comes with 3.5mm audio output on device;



TFT Lcd with a size of 1.77 inch color screen embedded, displaying unit identity, speaking mode, speaking status and speaking time;



Metal base, durable, beautiful and appeals to fashion, no fading and deformation;



Excellent anti-interference ability of mobile phone;



The conference unit supports hot plug function and is equipped with 2.1m 8p connecting cable; Hand in hand connection mode, easy installation and flexible operation;

## SPECIFICATION

Model NO.	EMCF1001L / EMCF1002L
Type	Capacitive Microphone
Polar Pattern	Unidirectional
Frequency Response	40Hz-16KHz
Sensitivity	-43 ± 2 dB @ 1 KHz
Input Voltage	DC 9V (Supplied by host)
Min Input impedance	1 KΩ
S / N Ratio	90dB
Input cable	2.0m 8p shielded wire
Accessory	Windproof sponge
Mic Length	480 mm