



## 8 Zone Paging Console EMMX-PG8 / EMMX-PG8E

EMIX EMMX-PG8 remote paging console is connected to EMMX-8x8 through industrial standard CAT5 cable for zone announcement or communication at a remote and different location from the control center.

### SPECIFICATIONS

Mic Input	5mV / 600Ω
Frequency Response	50Hz – 18kHz (±2dB)
S/N Ratio	> 75dB
THD	< 0.1% at 1kHz
Signal Output	0.775V / 600Ω
Indication	Individual zone, All zone, Busy, Paging, Output signal level indicator
Protection	DC 24V / 2A, Revert fuse protection
Power Supply	DC 24V
Dimension (W × D × H)	180 × 143 × 52mm
Weight	2.5kg



## Control Panel C/w Audio And Mic Input EMMX-CP1

EMIX EMMX-CP1 control panel is connected to EMMX-8x8 through industrial standard CAT5 cable to select the source and volume adjustment.

### SPECIFICATIONS

Mic Input Sensitivity	5mV / 600Ω, Phantom Power: 12V
Aux Input Sensitivity	350mV / 10kΩ
Audio Output	0db / 600Ω
Frequency Response	50Hz – 18kHz (±1dB)
S/N Ratio	Mic: >65dB Aux: >75dB
THD	< 0.1% at 1kHz
Communication Port	RJ45
Communication Protocol	RS485
Serial Communication Speed	4800bps
Power Supply	DC 24V (From CAT5)
Power Consumption	5W
Dimension (W × H × D)	146 × 86 × 48mm
Weight	500g
Material and Finishing	Grey & Aluminum