

TA-8011
Pre. Amplifier



TA-8011 Pre. Amplifier Mixer

The Pre amplifier Mixer is equipped with 12 inputs, which are 3 unbalance MIC inputs, 3 imbalance Aux inputs, 2 balance Aux inputs, 2 priority inputs and 4 outputs. The front panel provide light touch button for ease of operation. Volume control, bass and treble tone controls are available for individual control. A display screens are provided at front panel for each input or output signal level, all working status are clear at a glance. The unit is ready with chime light touch button in order to precede the chime tone. The pre amplifier can be remotely configuration/control/monitor/diagnose by PC and capable for its system link-up via data port at rear panel.

Features:

- » Microprocessor based control, soft touch button
- » 12 inputs , 1 Output
- » Individual volume control, master tone control
- » LED display for each input/output signal level,
 - » Chime and mute function
- » Network PC control

Technical Specifications

TA-8011 Pre. Amplifier	
Input	Mic 1,2,3 : 600Ω, 2.5 mV, unbalance Mic 4,5 : 600Ω, 2.5 mV, balance EMC 1,2; Aux 1,2,3 : 10 kΩ, 250 mV, unbalance Aux 4,5 : 10 kΩ, 250 mV, balance
Audio output	0 dBV
Frequency Response	20Hz-25kHz, Line in
Gross wave distortion	0.003%
Signal/noise ratio	Mic input : 80 dB Aux input : 85 dB
Tone	Bass : ± 10dB at 100 Hz Treble : ± 10dB at 12 kHz
Chime	Press the button once, the tune is “(1-3-5-1)”, Volume adjustable
Protection	AC fuse x 1
Power Requirement	1. AC 230V/50~60Hz 2. DC24V
Dimensions	485 x 88 x 375 mm
Net Weight	5.8 kg

Specifications are subject to change without prior notice