

TA-8922 Coaxial Ceiling Loudspeaker

The TA-8922 full range coaxial ceiling loudspeaker of a combination of quality, acoustic performance and innovation in public address system. They are suitable for excellent speech intelligibility and back ground music of all application. It is surprising high frequency coverage with bass response and meet virtually all sound reinforcement system requirement.



A circular stainless steel grille is an integrated with fireproofing acoustic damping enclosure protect against speaker and termination. Its built-in 70 / 100V line matching transformer with multi tapping power output. The unit is screw visible use spring clamping into a hole in suspended ceiling or wall boards.

The loudspeaker used in application airport terminals, bus / railway stations, sport / convection halls, hotels, hospitals, restaurants, office, department stores.

Features:

- » Full range coaxial ceiling loudspeaker
- » Stainless steel perforated grille
- » Excellent speech and back ground music reproduction
- » Wide angle coverage
- » Fireproofing acoustic damping enclosure

Technical Specifications

Speaker	4"x1 , 2"x 1
Normal Power	8W
Max. Power	15W
Sound Pressure Level	101dB
Sensitivity (1W, 1M)	88dB
Frequency Response	130 ~ 20kHz
Rated Voltage	70 / 100V Line
Opening Mounting Hole	200mm
Dimension (W x H)	220 x 115mm
Net Weight	2 kg