

# EMRM-800

## Remote Paging Console



The **EMIX** EMRM-800 is a desktop call station with a discreet and flexible/adjustable gooseneck microphone. It is designed specifically to page/call selected zones (1 to 100 zones or All zones) in a building's PA system. EMRM-800 is designed with a stable and solid metal base. EMRM-800 is to be used in conjunction with EMRM-810.

### Features

- > 100 zones call station
- > Up to 100 zones selection keys and all-call key
- > Chime function (Adjustable chime volume)
- > Built-in with 2 different chime
- > Muting function, signal from "LINE" will be automatically muted by signal from MIC1 or Chime.
- > Remote paging for up to 300 meters
- > Able to control up to 10 units of EMRM-810
- > Built-in microphone
- > LED output level indicator

Model	EMRM-800
Input	Mic : $70 \pm 10\text{mV}$ , unbalanced Line : $1 \pm 0.1\text{V}$ , unbalanced
Audio Output	$1 \pm 0.1\text{V}$
Frequency Response	Mic : 100Hz-15kHz Line : 50Hz-20kHz ( $\pm 3\text{dB}$ )
Signal To Noise Ratio	Mic input : Greater than 60dB Line input : Greater than 70dB
Power Requirement	From EMRM 810
Dimensions (W x H x D)	270 x 180 x 55mm
Gross Weight	1.5kg
Net Weight	1.2kg

### Rear View



### Schematic Diagram

